

Dimlux Xplore 730W Compact 9x 3.0

Building on the success of the Xplore Series, the all-new Dimlux Xplore Series 730W 3.0 brings cutting-edge innovation, enhanced efficiency, and superior light distribution to growers worldwide. An investment in the Xplore 3.0 is a commitment to the best performance-to-cost ratio in the market, making it the smart choice for growers seeking maximum returns with reliable, high-quality lighting solutions.



Key Benefits of the Xplore Series

Exceptional Performance: Industry-leading efficiency and light distribution deliver high yields with minimal energy usage.

Uniform Light Distribution: Asymmetrically placed LEDs ensure even coverage, improving growth and flowering across the canopy.

Future-Proof Design: Expandable with UV and far-red add-ons, backed by a 3-year warranty for peace of mind.

Proven ROI: Affordable entry price ensures quick payback, putting high-performance LED lighting within reach.

What's new?

- System efficiency 3.0 $\mu\text{mol/J}$
- Unbreakable lens with light benders
- IP68 Quick Lock Power Connector
- Integrated LED driver
- 5-year warranty

Designed and engineered in the Netherlands.

Dimlux has again invested in R&D and delivers with the Xplore series very high efficiency and light output scores with an unparalleled light distribution. In addition, the fixtures are future proof. Dimlux naturally offers a 5-year warranty on the Xplore fixtures. And for the ambitious grower who wants to go the extra mile now or later for even better growth yield, expansions are possible to create the ideal set-up..

- XPLORE SERIES 730W 3.0 LE 730W
- Light Source LED 730W
- Light Output (PPF) 2160 $\mu\text{mol/s}$
- Light Output Total (PPF 350-800nm): 2197 $\mu\text{mol/s}$
- PAR Photon Efficacy (400-700nm) 3.0 $\mu\text{mol/J}$ @ 230-240V AC
- Total Photon Efficacy (350-800nm) 3.02 $\mu\text{mol/J}$ @ 230-240V AC
- AC Input Power 730W @ 230-240V AC
- AC Input Voltage 200-277V AC, 50/60Hz



- driver 730W Integrated High Voltage LED Driver
- Spectrum Full Spectrum White and Red LED Diodes
- Beam Angle 110°
- Optics High Transmittance Lens With Light Benders
- LED position Asymmetrical
- Rcmd Mounting Height 150x150cm, min. 40cm / 4.9x4.9', min. 1.3'
- Max. Ambient Temperature -25 ~ 40°C / -13 ~ 104°F
- Control By Dim Button or MaxiController
- Total Harmonic Distortion (THD) < 10%
- Lifetime L90 > 50,000h
- IP Rating IP44
- Certifications CE, DLC Listed, UKCA,CASA, ETL
- Warranty 5 YEAR STANDARD
- Measurements 1164×1063×38mm 45.83×41.85×1.50 inch
- Weight 7.40kg / 16.30 lbs

Klik om naar het product: [Dimlux Xplore 730W Compact 9x 3.0](#) te gaan.